# 

## Wire&Cables



### Product: PKJ 5205

Application	Light Color Wire&Cables	
Туре	Ca Zn	
Typical Addition	4.0 - 5.5	
Heat Loss (%)	≤2.0	
Lubrication	**	
Form	Powder	

#### **Typical Formulation**

Material	Sheathing	Insulation
PVC SG-3	100	100
DOP	50	/
DIDP	/	55
CaCO <sub>3</sub>	60-80	30-50
PKJ 5203	4.0-5.5	4.0-5.5
Lubricant	0.5-1.0	0.5-1.0
Pigment	As needed	As Needed

#### **Properties**

PKJ 5205 is an CaZn based onepack stabilizer suitable for UL60<sup>°</sup>C white or light color wire and cable products. It can also be applied in other white or light color soft PVC products. This product offers such property such as good initial color and color hold, good weather durability with excellent product physical property. It will be better in combination with soybean oil and polyalcohol chemicals.

No lubrication component is added in PKJ 5205, customers can add the internal and external lubrication according to the actual processing requirements.

PKJ 5205 is conformed with the EU ROHS, REACH and other environmental standard.

All raw materials and every batch of one pack are tested to a high standard to ensure product consistency and meet the high quality demands of the customer. A quality assurance certificate can be provided for each product batch according to customer's request and supported by our ISO 9001:2008 Quality management system.

#### Package

Valve side paper/PE bag(25kg N.W) or plastic woven container sack. Period of quatity guarantee is one year.

#### Storage

Stored in dry place, to avoid high temperature, keep away from acid, alkali and other corrosive substances.

#### NANJING JINLING CHEMICAL CO., LTD.

 Add:No.55, NJC Road, Chemical Industry Park Nanjing China.
 Post Code: 210047

 Tel: (025) 85315451, 84712677, 84716016
 Fax: (025) 85315451

 Email: angel.cai@njchem.net
 Web: www.njchem.net